



Section 1 Chemical Product and Company Identification

Product identifiers

Master KINCOTE Vermillion

Relevant identified uses of the substance or mixture and uses advised against

Lacquer pattern coating. For industrial and professional use only.

Details of the supplier of the safety data sheet:

Freeman Manufacturing & Supply Company
1101 Moore Road, Avon, OH 44011-4043 USA
Telephone: +1 800 321-8511
Email: contactus@freemansupply.com

24-Hour Emergency Telephone Number
CHEMTREC: (800) 424-9300

Section 2 Hazards Identification

GHS Classification in accordance with 29 CFR 1910.1200 (OSHA HCS)

Flammable Liquid, Category 2
Acute Toxicity, Inhalation, Category 4
Aspiration Hazard, Category 1
Carcinogenicity, Category 2
Eye Irritation, Category 2A
Skin Irritation, Category 2
Single Target Organ Toxicity, Single Exposure, Nervous System, Category 3

GHS Label elements, including precautionary statements



Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H332 Harmful if inhaled.
H304 May be fatal if swallowed and enters airways.
H351 Suspected of causing cancer.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Use personal protective equipment as required.
P363 Wash contaminated clothing before reuse.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352 IF ON SKIN: Wash with plenty of water.



Section 2 Hazards Identification

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P370+P378 In case of fire: Use dry chemical, carbon dioxide, or foam to extinguish.
 P403+P233 +P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local rules and regulations.

Section 3 Composition/Information on Ingredients

Ingredient Name	CAS Number	Weight %
Isobutyl Acetate	110-19-0	25-50
2-Propanol	67-63-0	2.5-10
m-Xylene	108-38-3	2.5-10
p-Xylene	106-42-3	2.5-10
Propylene Glycol Monomethyl Ether Acetate	108-65-6	2.5-10
Ethyl Benzene	100-41-4	2.5-10
o-Xylene	95-47-6	2.5-10

Section 4 First Aid Measures

If inhaled: Move person into fresh air. If not breathing, give artificial respiration. If irritation persists, get medical assistance.
In case of skin contact: Wash off with soap and plenty of water. If skin irritation continues, consult a doctor.
In case of eye contact: Remove contact lenses, if worn. Flush opened eyes thoroughly with water. If irritation persists, get medical assistance.
If swallowed: Harmful if swallowed, seek medical advice immediately.

Section 5 Fire-Fighting Measures

Suitable extinguishing media: Use alcohol-resistant foam, dry chemical or carbon dioxide.
Unusual fire and explosion hazards: Remove all sources of ignition.
Advice for firefighters: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Wear self-contained breathing apparatus for firefighting if necessary.

Section 6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures
 Avoid breathing vapors, mist or gas. Remove all sources of ignition. Ensure adequate ventilation. Remove all non-essential people from the area. For personal protection see section 8.
Environmental precautions
 Do not let product or firefighting foam enter drains.



Section 6 Accidental Release Measures

Methods and materials for containment and cleaning up

Soak up with inert absorbent material and keep in suitable, closed containers for disposal.

Section 7 Handling and Storage

Precautions for safe handling

Use normal precautions when handling flammable materials. Do not breathe fumes or vapor. Do not allow material to contact skin. Provide appropriate exhaust ventilation.

Conditions for safe storage

Store at ambient temperatures in closed containers. Keep in a well-ventilated place. Store away from foodstuffs. This material can catch fire if overheated. Do not heat this material above the flash point. Keep away from flame and open electrical coils.

Section 8 Exposure Controls/Personal Protection

Components with workplace control parameters

Ingredient	OSHA		ACGIH	
	PEL-TWA	PEL-Ceiling	TLV-TWA	TLV-STEL
Isobutyl Acetate	150 ppm	Not established	150 ppm	Not established
2-Propanol	400 ppm	Not established	200 ppm	400 ppm
m-Xylene	100 ppm	Not established	100 ppm	150 ppm
p-Xylene	100 ppm	Not established	100 ppm	150 ppm
Ethyl Benzene	100 ppm	Not established	100 ppm	125 ppm
o-Xylene	100 ppm	Not established	100 ppm	150 ppm

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits. An eyewash station and safety shower should be located near the workstation.

Personal protective equipment

Eye/face protection: Wear safety glasses equipped with side shields.

Hand protection: Wear disposable nitrile gloves. Contaminated gloves should be replaced.

Body protection: Prevent skin contact when handling material.

Respiratory protection: The need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist pre-filter should be used.

General Hygienic Practices

Avoid breathing vapor or mist. Avoid contamination of food, beverages, or smoking materials.

Wash thoroughly after handling, and before eating, drinking or smoking.

Remove contaminated clothing promptly and clean thoroughly before reuse.

Section 9 Physical and Chemical Properties

Appearance	Dark red heavy liquid
Odor	Characteristic solvent
Odor Threshold	No data available
pH	No data available
Melting Point/Freezing Point	No data available
VOC	620 g/L



Section 9 Physical and Chemical Properties

Boiling Range	177-536°F
Flash Point (CC)	44.6°F (7°C)
Evaporation Rate	7.70
Flammability (solid, gas)	No data available
Upper/lower flammability	No data available
Vapor Pressure	33.0 mmHg
Vapor Density	4.60
Specific Gravity	0.984
Water Solubility	No data available
Coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Viscosity	No data available
Explosive Properties	No data available
Oxidizing Properties	No data available

Section 10 Stability and Reactivity

Reactivity	No data available
Chemical stability	Stable under recommended storage conditions
Conditions to avoid	Heat and open flames
Incompatible materials	Strong oxidizing agents
Hazardous decomposition	Carbon monoxide, carbon dioxide

Section 11 Toxicological Information

Effects of Overexposure

Inhalation: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

Skin contact: Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

Eye Contact: Direct eye contact may cause irritation.

Ingestion: Harmful; may cause lung damage if swallowed.

Acute Toxicity Values

Ingredient Name	CAS Number	Oral LD50	Dermal LD50
2-Propanol	67-63-0	5000	12800
p-Xylene	106-42-3	4300	2000
Ethyl Benzene	100-41-4	3500	17800
o-Xylene	95-47-6	4300	2000

Germ cell mutagenicity	No data available
Carcinogenicity	No data available on this product
Reproductive toxicity	No data available

Section 12 Ecological Information

Ecotoxicity	No data available
Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in soil	No data available
Results of PBT & vPvB assessment	No data available



Section 13 Disposal Considerations

Contact waste disposal services. Dispose of in accordance with all local, state and federal regulations.

Section 14 Transport Information

DOT

UN Number: 1263
Proper Shipping Name: Paint, Flammable Liquid
Hazard Class: 3
Packing Group: II
Label: Flammable Liquid
Response Guide Page: 128

Section 15 Regulatory Information

U.S. Federal Regulations

Superfund Amendment and Reauthorization Act of 1986 (SARA Title III), Sections 311 and 312:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Aspiration Hazard

SARA 313 Toxic Chemical

Chemical Name	CAS Number
2-Propanol	67-63-0
m-Xylene	108-38-3
p-Xylene	106-42-3
Ethyl Benzene	100-41-4
o-Xylene	95-47-6

Toxic Substance Control Act (TSCA): All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

U.S. State Regulations

California Proposition 65: ⚠️ **WARNING:** This product can expose you to chemicals including ethyl benzene and toluene, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Section 16 Other Information

HMIS Ratings: Health: 2 Flammability: 3 Reactivity: 0 Personal Protection: X

Disclaimer

The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.

Initial release date: December 1, 2015
 Date of previous revision: July 6, 2018
 Current revision date: July 2, 2025