

5700 Skylab Road Huntington Beach CA 92647 USA Phone : +1 714-899-8100 Fax : +1 714-899-8179 E-mail : airtech@airtechintl.com Website : www.airtechonline.com

Data Sheet

GS-100

Multi-purpose sealant tape up to 375°F (191°C)

DESCRIPTION

GS-100 is a multi-purpose vacuum bag sealant tape that works well with composite or metal tools. It is suitable for cure applications up to 375°F (191°C).

BENEFITS

- Multi-purpose tape is good with metal and composite tooling.
- Provides an excellent vacuum seal for efficient vacuum bagging.
- Tape is easy to use, making vacuum bagging faster.

TECHNICAL DATA

Color Base material Maximum use temperature Shelf life Reddish brown Synthetic rubber 375°F (191°C) 12 months from date of manufacture Tape must be stored flat in original packaging at 72°F (22°C) Do not refrigerate

Storage conditions

SIZES

Dimensions	Packaging
1/8 inch x 1/2 inch x 25 feet (3 mm x 12mm x 7.5 m)	40 rolls per case



NOTES

• For clean removal, it is recommended to strip the tape from the mold surface once it has cooled down to room temperature.

• The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated : 2015-08-21

Catalog position : Vacuum bag sealant tapes

As the conditions or methods of use, including storage, are beyond our control, Airtech International, Inc. does not assume responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech International, Inc. disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes. Any translation is provided for your convenience only. The official language is English and the official law is California, USA.