5700 Skylab Road Huntington Beach CA 92647 USA Phone: +1 714-899-8100 Fax: +1 714-899-8179 E-mail: airtech@airtechintl.com Website: www.airtechonline.com

## **Data Sheet**

**GS-213-3** 

# Higher temperature version of GS-213

#### DESCRIPTION

GS-213-3 is a higher temperature version of GS-213. It has slightly lower tack and excellent clean-up on any surface. It is usable up to 450°F (232°C).

### BENEFITS

- Lower tack level, so vacuum bags can be easily repositioned.
- High temperature rating for safer high temperature cures.
- Removes cleanly after cure reducing cost of tool cleaning.

#### TECHNICAL DATA

Color Light green
Base material Synthetic rubber
Maximum use temperature 450°F (232°C)

Shelf life 12 months from date of manufacture

Storage conditions

Tape must be stored flat in original packaging at 72°F (22°C)

Do not refrigerate

### SIZES

Dimensions	Packaging
1/8 inch x 1/2 inch x 25 feet (3 mm x 12 mm x 7.5 m)	32 rolls per case
1/8 inch x 3/4 inch x 25 feet (3 mm x 19 mm x 7.5 m)	20 rolls per case



#### NOTES

- For clean removal, it is recommended to strip the tape from the mold surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated: 2015-08-21