



DATA SHEET

AIRKAP 1 Polyimide High Temperature Pressure Sensitive Tape

Description

Airkap 1 is a polyimide pressure sensitive tape coated with a fully cured silicone adhesive for high temperature lay-ups to 750°F (399°C).

APPLICATION

Airkap 1 is used to hold down peel plies, breathers, vacuum bag pleats, thermocouples, etc. on high temperature cures, in an oven or autoclave. **Airkap 1** will hold down the exposed edges of Thermalimide bagging film in order to insulate A800-3G high temperature sealant tape.

Material Characteristics	
Carrier Type:	Polyimide
Adhesive Type:	Silicone
Total Thickness, in (μ):	.0025 (63)
Film Thickness, in (μ):	.001 (25)
Adhesive Thickness, in (μ):	.0015 (38)
Adhesion, oz/in-width (N/cm-width):	20 (2.2)
Elongation, %:	50
Maximum Recommended Use Temperature, °F (°C):	750 (399)
Color	Amber
Standard Sizes ⁽¹⁾ :	1" (2.54cm) x 36 yards (33m)
	2" (5.08cm) x 36 yards (33m)
Shelf Life:	1 year when stored at 72°F (22°C)

- 1) Other widths available.

CATALOG POSITION: PRESSURE SENSITIVE TAPES

As the conditions or methods of use are beyond our control, Airtech International, Inc. does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech International, Inc. disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes.

MORE THAN A MANUFACTURER...A TECHNICAL PARTNER!

