

DATA SHEET

P.T.F.E Coated Fiberglass Fabrics

Description

Release Ease P.T.F.E Coated Fiberglass Fabrics will provide release from all conventional resin systems. Porous products will allow excess resin, volatiles and trapped air to escape into the breather during cure while non-porous products will retain resin. **Release Ease** products have a continuous service temperature to 550°F (288°C).

Products

Release Ease 234TFP	Porous 1080 style glass fabric
Release Ease 234TFP-HP	1080 style glass fabric with reduced PTFE content for increased porosity
Release Ease 234TFP-1	Porous 104 style glass with a reduced thickness of .001(25µ)
Release Ease 234TFNP	Non-porous 1080 style glass
Release Ease 236TFNP	Non-porous 2116 style glass with increased thickness and PTFE content to reduce fabric mark-off

Available Sizes

	Roll Size	Total Thickness	Availability
Release Ease 234TFP	38" (97cm) x 100 yds. (91.4m)	.003 (75µ)	Stock
Release Ease 234TFNP	50" (127cm) x 100 yds. (91.4m)	.003 (75µ)	Stock
	60" (152cm) x 100 yds. (91.4m)	.003 (75µ)	Special Order
	72" (183cm) x 100 yds. (91.4m)	.003 (75µ)	Special Order
	80" (203cm) x 100 yds. (91.4m)	.003 (75µ)	Special Order
Release Ease 234TFP-HP	38" (97cm) x 100 yds. (91.4m)	.003 (75µ)	Stock*
Release Ease 234TFP-1	38" (97cm) x 100 yds. (91.4m)	.001 (25µ)	Stock*
Release Ease 236TFNP	38" (97cm) x 100 yds. (91.4m)	.006 (150µ)	Stock*

*Other thicknesses and sizes available on request. Minimum order may apply.

Roll width tolerance is $\pm \frac{1}{2}$ " (12.5mm)

All materials have an 18 month shelf life.

Color is subject to slight variation and does not affect performance.

CATALOG POSITION: **RELEASE FABRICS**

As the conditions or methods of use are beyond our control, Airtech International, Inc. does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech International, Inc. disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes.

MORE THAN A MANUFACTURER...A TECHNICAL PARTNER!

