

**1848****UNIDIRECTIONAL FABRIC****TYPICAL CONSTRUCTION**

<b>WARP RAW MATERIAL</b>	12K T700 Multifilament Continuous Tow
<b>FILLING RAW MATERIAL</b>	225 1/0 Hot Melt
<b>WEAVE STYLE</b>	Plain Weave
<b>FABRIC AREAL WEIGHT</b>	300 gsm approx.
<b>WARP ENDS/INCH</b>	9.0 +/- 1.0
<b>PICK/INCH</b>	5.0 +/- 1.0
<b>NOMINAL THICKNESS</b>	.022 inches
<b>FABRIC WIDTH</b>	24 +/- .025

**GENERAL INFORMATION**

<b>FRINGE EDGE TRIM</b>	.25 inches +/- 0.0625
<b>LENO MATERIAL</b>	N/A
<b>SELVAGE MATERIAL</b>	225 1/0 Hot Melt
<b>TRACERS</b>	None
<b>ROLL LENGTH</b>	Target 100 yards
<b>CORE SIZE</b>	3 inch inner diameter tubes
<b>FABRIC ROLL</b>	Fabric is to be tightly wound onto core as to prevent telescoping. Fabric roll is to be packaged in cardboard box with appropriate spacer and packaging materials so as to avoid shifting during the shipping process.
<b>CERTIFICATION</b>	Yes
<b>FDI PRODUCT #</b>	1848