



Release Innovation™

PRODUCT DATA SHEET

# Mono-Coat® RM-2145W

## Anti-Static Additive

### Description

Mono-Coat® RM-2145W is a water release system that provides anti-static properties, improves roll mixture, and provides a low frictional surface.

### Typical Properties

Appearance	Clear fluid
Density, lbs/gal; kg/l	8.35; 1.00
Storage Stability, unopened	12 months

### Recommended Uses

Mono-Coat® RM-2145W is an additive for rotational molding operations of all resin types.

### Application

Uniformly mix with resin or other host material. Addition of Mono-Coat® RM-2145W in the range of 0.25% - 1.0% by-weight is usually adequate to achieve the final desired properties in the host material.

Pounds of Host Material	Pounds of Mono-Coat® RM-2145W
100	0.25
5,000	12.50
20,000	50

### Storage

Do not store at temperatures above 100°F / 38°C. Keep container tightly sealed to prevent evaporation and/or moisture contamination. If stored in cold temperatures, allow product to warm to room temperature prior to use.

### Handling

We believe Mono-Coat® RM-2145W has a low degree of hazard when used as intended. For more information, request a copy of Chem-Trend's Safety Data Sheet.

### Further Information

Request information on our complete range of materials: custom-formulated release agents for polyurethane molding; tire lubes and bladder coatings; Mono-Coat® semi-permanent release coatings; aerosol formulations; mold cleaners and sealers; specialized coatings; and application equipment.

*While the technical information and suggestions for use contained herein are believed to be accurate and reliable, nothing stated in this bulletin is to be taken as a warranty either expressed or implied.*



DISTRIBUTED BY  
Freeman Mfg. & Supply Co.  
[www.FreemanSupply.com](http://www.FreemanSupply.com)