



Freeman 1030 Polyurethane Reinforcement Paste

Description

Freeman 1030 is a fiber-filled urethane paste that is perfect for creating strong, yet lightweight back-up for flexible urethanes, silicones, or epoxies. Features include easy mixing (1:3 ration by volume), easy application without sagging, low shrinkage, a quick 9 minute gel time, and a fast 90 minute handling strength.

Physical Properties

Color (mixed)	Tan
Mix Ratio (by weight)	41:100
Mix Ratio (by volume)	1:3
Viscosity (cps, mixed)	Paste
Gel Time (minutes @ 72°F)	9
Demold Time (hours)	1.5
Hardness (Shore D)(ASTM D2240)	70
Specific Gravity (mixed)	1.04
Volumetric Yield (cu. in./lb.)(ASTM D792)	26.7

Ordering Information

SKU	Description	Size	Net wt.
055418	Freeman 1030 Polyurethane	Gallon Kit	11.40 lbs.

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no event shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT

