

Technical Data Sheet

MiaGel F-944 Neutral Polyester Gelcoat

Description

MiaGel F-944 is neutral in color, enabling the user to custom color this product as desired. Use polyester color pastes only. MiaGel F-944 is specifically designed for making high quality fiberglass reinforced molds and parts. Applied using spray equipment, this product is sag resistant and fast curing. This room temperature curing product should be catalyzed with methyl ethyl ketone peroxide (MEKP).

Physical Properties

| Color | Neutral |
|---------------------|--------------------------------|
| Mix Ratio (by wt) | 1.2 to 3.0% (1.8% recommended) |
| Viscosity (cps) | 11,000 – 16,000 |
| Gel Time (minutes) | 10-17 |
| Demold Time (hours) | 24 |

Ordering Information

| SKU | Description | Size | Net wt. |
|--------|----------------------------|--------|---------|
| 411760 | MiaGel F-944 Resin Gallon | Gallon | 8.8 lbs |
| 412162 | MEKP Liquid Hardener 1 oz. | 1 oz. | 1 oz. |

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no event shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT