



## Master Wood Glue

### Description

Master Wood Glue is a high viscosity, fast setting, general purpose adhesive, designed for face gluing of wood or similar materials, doweling, and laminating of veneer or high pressure laminates.

### Physical Properties

|                      |       |
|----------------------|-------|
| Color (wet)          | White |
| Color (dry)          | Clear |
| Freeze Thaw Stable   | No    |
| Min Use Temperature  | 55°F  |
| Solids (~)           | 52%   |
| Specific Gravity (~) | 1.09  |
| Viscosity (cps)      | 5,600 |

### Directions:

Use freshly machined stock free from dirt or oil. Apply to one side of stock with brush roller or roll spreader. Assembly time is 10-20 minutes depending on temperature, moisture content, species, and porosity. Clamp time is 45-120 minutes depending on conditions. Allow to cure 24 hours before machining.

### Clean Up and Storage:

Cleans up easily with warm water while wet. Store between 55°-80°F. Use polyurethane, aluminum, or fiberglass containers.

### Ordering Information

| SKU    | Description                | Size     | Net wt. |
|--------|----------------------------|----------|---------|
| 022700 | White Wood Glue – Fast Set | Gallon   | 9 lbs   |
| 022705 | White Wood Glue – Fast Set | 5 Gallon | 45 lbs  |

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no event shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT