



Master Wood Glue

Description

Master Wood Glue is a high viscosity, fast setting, general purpose adhesive, designed for face gluing of wood or similar materials, doweling, and laminating of veneer or high pressure laminates.

Physical Properties

Color (wet)	White
Color (dry)	Clear
Freeze Thaw Stable	No
Min Use Temperature	55°F
Solids (~)	52%
Specific Gravity (~)	1.09
Viscosity (cps)	5,600

Directions:

Use freshly machined stock free from dirt or oil. Apply to one side of stock with brush roller or roll spreader. Assembly time is 10-20 minutes depending on temperature, moisture content, species, and porosity. Clamp time is 45-120 minutes depending on conditions. Allow to cure 24 hours before machining.

Clean Up and Storage:

Cleans up easily with warm water while wet. Store between 55°-80°F. Use polyurethane, aluminum, or fiberglass containers.

Ordering Information

SKU	Description	Size	Net wt.
022700	White Wood Glue – Fast Set	Gallon	9 lbs
022705	White Wood Glue – Fast Set	5 Gallon	45 lbs

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no event shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT

