



## Bacolac Professional Sandable Sealer

### Description

Bacolac is a clear lacquer sanding sealer which is specifically formulated as a high-build, easily sandable coating for sealing and smoothing wood, plaster, and other porous surfaces. A minimum of two coats is suggested, sanding after each application. Additional layers may be applied to more completely fill wood grain or surface porosity. May be applied using a pure bristle brush or by spray equipment. Bacolac Reducer should be used for spray applications and clean up. Stir completely prior to use.

### Features

- Fast Drying (30-45 minutes) between applications
- Allow 16-18 hours before use
- High solid content to fill grain and porosity with fewer applications
- Sands quickly and easily to produce smooth surface finishes
- Suitable for sealing master patterns for use with our tooling plastics
- Able to be thinned for spray applications (use Bacolac Reducer only).  
Add up to 10% of reducer for brushing application, and 10-20% to thin for spraying application.

### Ordering Information

Item Number	Description	Size	Net Wt. Lbs.
054531	Bacolac Sandable Sealer	Gallon	8.0
054532	Bacolac Reducer	Gallon	7.0

The user shall determine the suitability of this product for this application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no event shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT