

A Quality Product from Hawkeye Industries Inc.

Duratec® Polyester **Sealer**



A low viscosity, rapid curing, penetrating sealer that anchors lacquers, urethanes, polyesters, vinyl esters and most epoxies to a variety of substrates

Usage

For surfacing composite plugs and patterns and for sealing woods and veneers, plaster, concrete, and GRP surfaces.

Features

Save time and add quality with Duratec Polyester Sealer.

Here's why you should choose Duratec Polyester Sealer—

Easy to apply – Spray, brush or roll.

Rapid curing—surfaces are ready for topcoats in 1 to 2 hours.

Deep penetration—allows primers and topcoats to bond to a variety of substrates.

Duratec Polyester Sealer

[823A Clear](#)
(Link to MSDS)



Hawkeye Industries Inc.

P O Box 415 Bloomington, CA 92316
Tel 909-546-1160; Toll Free 800-977-0060; Fax: 909-546-1161
Email productinfo@duratec1.com Web www.duratec1.com

Liability/warranty statement: Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.

Duratec is a registered trademark of Dura Technologies Inc.

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511





Product No. 823 Clear

Duratec Polyester Sealer

Data Sheet
Continued

Pg. 2

Product Properties

All time calculations are based on temperatures of 77°F, 25°C

Viscosity

As measured on a Brookfield

Viscometer Model RVF,

Spindle #2 at 20 rpm

80 cps

Thixotropic Index

0

Gel Time

Sample based on a 100 g mass

catalyzed at 2 percent with mekP

14-16 min

Weight per Gallon

8.59 lb., 3.89 kg

Link to Application Guides for Duratec Polyester Sealer:

- [Priming and Leveling Application: Wood and MDF Surfaces](#)
- [Topcoating Application: Wood and MDF Surfaces](#)
- [Sealing, Fairing, Priming and Surfacing Application: Plugs, Patterns and Models](#)
- [Surfacing Application: Plaster Plugs and Molds](#)

Duratec Polyester Sealer is among the many fine Duratec products marketed world-wide by Hawkeye Industries Inc.

[📁 Contents/Literature CD](#) [📁 Trouble Shooting Guide](#)

Rev 9-14-05



Hawkeye Industries Inc.

P O Box 415 Bloomington, CA 92316

Tel 909-546-1160; Toll Free 800-977-0060; Fax: 909-546-1161

Email productinfo@duratec1.com Web www.duratec1.com

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511



Liability/warranty statement: Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.

Duratec is a registered trademark of Dura Technologies Inc.