



Tapping Wax

Description

Tapping Wax provides a clean, fast and precision method for tapping blind holes while also extending tap life. After the blind hole has been drilled, a solid piece of tapping wax of the proper diameter is placed in the hole. When the hole is tapped, the chips are embedded in the wax and carried out through the tap flutes. The chips do not pack in the bottom of the threaded hole. The tapped hole is now clean and ready to use, no blowing out is needed.

Physical Properties

Color	Light Yellow
Specific gravity	0.90 (+/-0.05)
Ring & Ball Softening Point (°F)	177 (+/-6)
Flash Point (°F)	465

Ordering Information

SKU	Description	Size	Net wt.
119636	Tapping Wax Stick ¼ x 6"	Box	1 lb.
119637	Tapping Wax Stick 5/16 x 6"	Box	1 lb.
119638	Tapping Wax Stick 3/8 x 6"	Box	1 lb.
119639	Tapping Wax Stick ½ x 6"	Box	1 lb.

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no event shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT