



SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Trade name : CLEAR HI-GLOSS ADDITIVE
 Type of product : Coating
 CAS-No. : mixture
 Product code : 904-001
 Formula : na
 Product group : Trade product

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Dura Technologies, Inc.
 2720 South Willow Avenue #A
 Bloomington, CA 92316

909-546-1162
 ChemTrec US: 800.424.9300
 ChemTrec Int: +1 70 3527 3887

1.4. Emergency telephone number

Emergency number : ChemTrec US: 800.424.9300 Int: +1 70 3527 3887

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flammable liquids Category 2 H225 Highly flammable liquid and vapour
 Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) :

Danger

Hazard statements (GHS CA) :

H225 - Highly flammable liquid and vapour

Precautionary statements (GHS CA) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/bond container and receiving equipment.
 P241 - Use explosion-proof electrical/ventilating/lighting equipment
 P242 - Use only non-sparking tools.
 P243 - Take action to prevent static discharges.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
 P370+P378 - In case of fire: Use media other than water to extinguish.
 P403+P235 - Store in a well-ventilated place. Keep cool
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

CLEAR HI-GLOSS ADDITIVE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN



SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Proprietary Resin	POLYMER	(CAS-No.) TRADE SECRET	<= 55	Not classified
styrene, inhibited	benzene, ethenyl- / cinnamene / phenylethylene / styrene / styrene, monomer / styrol / vinylbenzene	(CAS-No.) 100-42-5	<= 36	Flam. Liq. 3, H226
methyl ethyl ketone	2-butanone / 2-oxobutane / 3-butanone / acetone, methyl- / Al3-07540 / butan-2-one / butanone / Caswell NO 569 / ethyl methyl ketone / EXXON methylethyl ketone / FEMA N°. 2170 / ketone, ethyl methyl- / meetco / MEK (= methyl ethyl ketone) / methyl 2-propanone / methyl acetone	(CAS-No.) 78-93-3	<= 18	Flam. Liq. 2, H225
cobalt(II) 2-ethylhexanoate	2-ethylhexanoic acid cobalt salt / CO 12 / cobalt 2-ethylhexoate / cobalt bis(2-ethylhexanoate) / cobalt octoate / cobaltous 2-ethylhexanoate / cobaltous octoate / Environmentally hazardous substance, solid, n.o.s. / hexanoic acid, 2-ethyl-, cobalt(2+) salt / NL 49P / NL 51P / NL 51S	(CAS-No.) 136-52-7	<= 0.9	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: wash thoroughly for five minutes. seek medical attention. Get medical advice/attention. Specific treatment (see seek medical attention. on this label). Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: SEEK IMMEDIATE MEDICAL ATTENTION. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center/doctor/physician if you feel unwell.
First-aid measures general	: Never give anything by mouth to an unconscious person. Suspected of causing cancer. IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. May cause genetic defects. Causes damage to organs.
Symptoms/effects after inhalation	: May cause respiratory irritation. Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Potential Adverse human health effects and symptoms	: Harmful if inhaled.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Sand. Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	: Do not use a heavy water stream.
--------------------------------	------------------------------------

5.3. Specific hazards arising from the hazardous product

Fire hazard	: Highly flammable liquid and vapour.
-------------	---------------------------------------

CLEAR HI-GLOSS ADDITIVE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN



- Explosion hazard : May form flammable/explosive vapor-air mixture.
Reactivity in case of fire : No reactivity hazard other than the effects described in sub-sections below.

5.4. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.2. Methods and materials for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released product, pump into suitable containers.
Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing DUST, FUMES, MIST, OR VAPORS. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Eliminate all ignition sources if safe to do so. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.
Hygiene measures : Wash HANDS thoroughly after handling. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, ventilating and lighting equipment. Ground/bond container and receiving equipment.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : HEAT SPARKS OR OPEN FLAMES. Keep in fireproof place. Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

styrene, inhibited (100-42-5)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - ACGIH	ACGIH STEL (ppm)	40 ppm
Ontario	OEL STEL (ppm)	100 ppm
Ontario	OEL TWA (ppm)	35 ppm
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Saskatchewan	OEL STEL (ppm)	40 ppm
Saskatchewan	OEL TWA (ppm)	20 ppm
Saskatchewan	Notations and remarks	T20

CLEAR HI-GLOSS ADDITIVE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**

methyl ethyl ketone (78-93-3)		
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	300 ppm
Alberta	OEL STEL (ppm)	300 ppm
Alberta	OEL TWA (ppm)	200 ppm
Alberta	Notations and remarks	URT irr; CNS & PNS impair
Manitoba	OEL STEL (ppm)	300 ppm
Manitoba	OEL TWA (ppm)	200 ppm
Manitoba	Notations and remarks	URT irr; CNS & PNS impair
New Brunswick	OEL STEL (ppm)	300 ppm
New Brunswick	OEL TWA (ppm)	200 ppm
New Brunswick	Notations and remarks	URT irr; CNS & PNS impair
Newfoundland & Labrador	OEL STEL (ppm)	300 ppm
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm
Newfoundland & Labrador	Notations and remarks	URT irr; CNS & PNS impair
Nova Scotia	OEL STEL (ppm)	300 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nova Scotia	Notations and remarks	URT irr; CNS & PNS impair
Nunavut	OEL STEL (ppm)	300 ppm
Nunavut	OEL TWA (ppm)	200 ppm
Nunavut	Notations and remarks	URT irr; CNS & PNS impair
Northwest Territories	OEL STEL (ppm)	300 ppm
Northwest Territories	OEL TWA (ppm)	200 ppm
Northwest Territories	Notations and remarks	URT irr; CNS & PNS impair
Ontario	OEL STEL (ppm)	300 ppm
Ontario	OEL TWA (ppm)	200 ppm
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL STEL (ppm)	300 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Prince Edward Island	Notations and remarks	URT irr; CNS & PNS impair
Saskatchewan	OEL STEL (ppm)	300 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure exposure is below occupational exposure limits (where available). Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

CLEAR HI-GLOSS ADDITIVE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Color	: clear
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: >= °C
Freezing point	: No data available
Boiling point	: >= 79.4 °C
Flash point	: >= 7 - 10 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour
Vapor pressure	: No data available
Vapor pressure at 50 °C	: No data available
Relative density	: <=
Specific gravity / density	: <= 1.05
Solubility	: No data available
Log Pow	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: No reactivity hazard other than the effects described in sub-sections below. Highly flammable liquid and vapour.
Chemical stability	: Polymerization can result in formation of solid deposits, even in vapour space. Highly flammable liquid and vapour. May form flammable/explosive vapor-air mixture.
Possibility of hazardous reactions	: Not established.
Conditions to avoid	: Direct sunlight. Extremely high or low temperatures. Open flame. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong acids. Strong bases.
Hazardous decomposition products	: fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

styrene, inhibited (100-42-5)	
LD50 oral rat	5000 mg/kg (Rat; Literature study; >6000 mg/kg bodyweight; Rat; Weight of evidence)
LD50 oral	> 6000 mg/kg body weight (Hamster, Male, Weight of evidence, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
LD50 dermal rabbit	5010 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	11.8 mg/l air (4 h, Rat, Inconclusive, insufficient data, Inhalation (vapours))
LC50 inhalation rat (ppm)	2770 ppm/4h (Rat; Literature study)
ATE CA (oral)	5000 mg/kg body weight

CLEAR HI-GLOSS ADDITIVE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**



styrene, inhibited (100-42-5)	
ATE CA (Dermal)	5010 mg/kg body weight
ATE CA (Gases)	2770 ppmV/4h
cobalt(II) 2-ethylhexanoate (136-52-7)	
LD50 oral rat	3129 mg/kg body weight (Rat; OECD 425: Acute Oral Toxicity: Up-and-Down Procedure; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Weight of evidence; OECD 402: Acute Dermal Toxicity)
ATE CA (oral)	3129 mg/kg body weight
methyl ethyl ketone (78-93-3)	
LD50 oral rat	2193 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Read-across, Oral)
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
ATE CA (oral)	2193 mg/kg body weight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
	: Not classified
STOT-repeated exposure	
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Harmful if inhaled.
Symptoms/effects	: Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. May cause genetic defects. Causes damage to organs.
Symptoms/effects after inhalation	: May cause respiratory irritation. Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Aquatic acute	: Not classified
Aquatic chronic	: Not classified

styrene, inhibited (100-42-5)	
LC50 fish 1	10 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	4.7 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value, GLP)
ErC50 (algae)	4.9 mg/l (EPA OTS 797.1050, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF fish 1	35.5 (Carassius auratus, Literature study)
Log Pow	2.96 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Log Koc	2.55 (log Koc, Estimated value)
cobalt(II) 2-ethylhexanoate (136-52-7)	
LC50 fish 1	46.51 mg/l (LOEC; ASTM; 96 h; Pimephales promelas; Flow-through system; Fresh water; Read-across)
LC50 fish 2	54.1 mg/l (LC50; ASTM; 96 h; Pimephales promelas; Flow-through system; Fresh water; Read-across)

CLEAR HI-GLOSS ADDITIVE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN



cobalt(II) 2-ethylhexanoate (136-52-7)	
EC50 Daphnia 1	0.212 mg/l (NOEC; ASTM; 48 h; Ceriodaphnia dubia; Static system; Salt water; Read-across)
EC50 Daphnia 2	0.605 mg/l (LC50; ASTM; 48 h; Ceriodaphnia dubia; Static system; Salt water; Read-across)
BCF fish 1	1.2 (BCF; 131 days; Seriola quinqueradiata; Static system; Salt water; Read-across)
Threshold limit algae 1	144 µg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Read-across)
Threshold limit algae 2	32.2 µg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Read-across)

methyl ethyl ketone (78-93-3)	
LC50 fish 1	2993 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	308 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Log Pow	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Log Koc	1.53 (log Koc, Calculated value)

12.2. Persistence and degradability

CLEAR HI-GLOSS ADDITIVE (mixture)	
Persistence and degradability	Not established.

styrene, inhibited (100-42-5)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Chemical oxygen demand (COD)	2.8 g O ₂ /g substance
ThOD	3.07 g O ₂ /g substance
BOD (% of ThOD)	0.42 (Literature study)

Proprietary Resin (TRADE SECRET)	
Persistence and degradability	Not established.

cobalt(II) 2-ethylhexanoate (136-52-7)	
Persistence and degradability	Readily biodegradable in water. No (test)data on mobility of the substance available.

methyl ethyl ketone (78-93-3)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Not established.
Biochemical oxygen demand (BOD)	2.03 g O ₂ /g substance
Chemical oxygen demand (COD)	2.31 g O ₂ /g substance
ThOD	2.44 g O ₂ /g substance

12.3. Bioaccumulative potential

CLEAR HI-GLOSS ADDITIVE (mixture)	
Bioaccumulative potential	Not established.

styrene, inhibited (100-42-5)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
BCF fish 1	35.5 (Carassius auratus, Literature study)
Log Pow	2.96 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Log Koc	2.55 (log Koc, Estimated value)

Proprietary Resin (TRADE SECRET)	
Bioaccumulative potential	Not established.

cobalt(II) 2-ethylhexanoate (136-52-7)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF fish 1	1.2 (BCF; 131 days; Seriola quinqueradiata; Static system; Salt water; Read-across)

methyl ethyl ketone (78-93-3)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.
Log Pow	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Log Koc	1.53 (log Koc, Calculated value)

12.4. Mobility in soil

CLEAR HI-GLOSS ADDITIVE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**



styrene, inhibited (100-42-5)	
Surface tension	0.032 N/m (20 °C)
Ecology - soil	Low potential for adsorption in soil.
Log Koc	2.55 (log Koc, Estimated value)
Log Pow	2.96 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)

cobalt(II) 2-ethylhexanoate (136-52-7)	
Surface tension	0.064 N/m (20 °C; 1 g/l)

methyl ethyl ketone (78-93-3)	
Surface tension	0.024 N/m (20 °C)
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.
Log Koc	1.53 (log Koc, Calculated value)
Log Pow	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)

12.5. Other adverse effects

Ozone	: Not classified
Other information	: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to approved disposal site.
Additional information	: Handle empty containers with care because residual vapors are flammable. Flammable vapors may accumulate in the container.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

Not regulated for transport

14.2. Transport information/DOT

Department of Transport

DOT NA No	: UN1866
UN-No.(DOT)	: 1866
Packing group (DOT)	: II - Medium Danger
Transport document description	: UN1866 Resin solution, 3, II
Proper Shipping Name (DOT)	: Resin solution
Contains Statement Field Selection (DOT)	:
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Division (DOT)	: 3
Hazard labels (DOT)	: 3 - Flammable liquid



Dangerous for the environment	: No
-------------------------------	------

CLEAR HI-GLOSS ADDITIVE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**



DOT Special Provisions (49 CFR 172.102)	: 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons). 383 - Packages containing toy plastic or paper caps for toy pistols described as "UN0349, Articles, explosive, n.o.s. (Toy caps), 1.4S" or "NA0337, Toy caps, 1.4S" are not subject to the subpart E (labeling) requirements of this part when offered for transportation by motor vehicle, rail freight, cargo vessel, and cargo aircraft and, notwithstanding the packing method assigned in §173.62 of this subchapter, in conformance with the following conditions: B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 173
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Emergency Response Guide (ERG) Number	: 127
Other information	: No supplementary information available.

14.3. Air and sea transport

IMDG

UN-No. (IMDG)	: 1866
Proper Shipping Name (IMDG)	: RESIN SOLUTION
Transport document description (IMDG)	: UN 1866 RESIN SOLUTION, 3, II
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger

IATA

UN-No. (IATA)	: 1866
Proper Shipping Name (IATA)	: Resin solution
Transport document description (IATA)	: UN 1866 Resin solution, 3, II
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. National regulations

styrene, inhibited (100-42-5)

Listed on the Canadian DSL (Domestic Substances List)

Proprietary Resin (TRADE SECRET)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

cobalt(II) 2-ethylhexanoate (136-52-7)

Listed on the Canadian DSL (Domestic Substances List)

methyl ethyl ketone (78-93-3)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

styrene, inhibited (100-42-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

CLEAR HI-GLOSS ADDITIVE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**



Proprietary Resin (TRADE SECRET)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

cobalt(II) 2-ethylhexanoate (136-52-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

methyl ethyl ketone (78-93-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour

SDS Canada (GHS)

To the best of our knowledge this SDS is accurate. The extent allowed by law, this statement is made in lieu of any other warranties, expressed or implied including but not limited to any implied warranty of merchantability or fitness for a particular purpose and is in lieu of any other obligations or liability on the part of Dura Technologies, Inc.